

# Hyper Impact Wrench

# SI-1610

SI-1610


SI-1610 SR

The max torque  
450Nm

148mm length

Super light weight  
Composite body  
Only 1kg

T valve trigger for easy speed control



Soft touch grip  
with twin molding

## SI-1610 SR

- Full power in reverse help to unfasten bolts quickly for changing wheels.



Multifunction Lever  
for easy operation

### SI-1610

- Rubber grip absorbs the vibration remarkably well and also protects your hand from the cold.
- Compact, lightweight, ergonomic design and a "feather touch" trigger for easy operation.
- Handle grip exhaust directs air away from operator and workplace.
- 3 positions regulator dial for easy adjustment.
- Muffer reduces noise level.

APPLICATIONS : Excellent tool for all types of small fasteners, automobile work and body shop.

### Specifiction : SI-1610 & SI-1610SR 1/2" IMPACT WRENCH

LENGTH	148mm	FREE SPEED(F)	8,000rpm	BOLT CAP	18mm/(11/16in.)
WIDTH	63mm	FREE SPEED(R)	8,500rpm	NOISE LEVEL	89dBA/(102power)
HEIGHT	174mm	MAXIMUM TORQUE	450Nm/(332ft-lb)	VIBRATION	4.0m/s <sup>2</sup>
WEIGHT	1.04kg	WORKING TORQUE RANGE	320Nm/(258ft-lb)	AVG AIR CONSUMPTION	3.8CFM

※The maximum torque was measured under our established conditions. It may differ from the actual working torque.

 PNEUMATIC TOOLS  
**SHINANO INC.**

<http://www.shinanoinc.com/>

Distributed by :